The new macro™ pipette controller – Optimized technology and ergonomic design!

macro™ Pipette Controller

The new macro™ pipette controller from BRAND – for comfortable and simple pipetting, with optimized technology and design:

- Draws liquids up rapidly with the newly designed suction bellow
- Easier, more sensitive meniscus adjustment with the new spring-loaded control lever
- Contoured design without corners and edges for convenient pipetting, even for long serial pipetting
- Four colors to choose from: gray, magenta, green, or blue, for better identification of different applications







Lab Rats Trust BrandTech!



Toll Free: 888-522-2726 www.brandtech.com

Macro_Flyer_BT_2015

New Design – optimized handling

Convenient operation without effort. The unique valve system allows for easy compression of the newly designed bellows. 50ml of fluid can be drawn in within just 11 seconds. The spring loaded lever enables an even more sensitive filling and delivery of liquids. The meniscus is easily adjustable.

Ergonomic design

The optimized design, the practical arrangement of functions, and the low weight of 125g offer reliable operation during serial pipetting tasks, even for inexperienced users.

Broad range of applications


One single macro pipette controller covers the entire range of bulb and graduated pipettes from 0.1 to 200ml. The conical silicone adapter offers a secure fit for the different diameters. The unit is fully autoclavable at 121°C (2 bar) according to DIN EN 285. A hydrophobic membrane filter protects the system from liquid penetration.

Perk up the lab with color

Four different colors: gray, magenta, green, and blue.

macro™ Pipette Controller		Catalog #
Gray		26200
Blue		26202
Magenta		26203
Green		26201

Accessories	Pack of	Catalog #
Membrane filter 3µm (PP, PTFE), non-sterile	1	26052
Membrane filter 3µm (PP, PTFE), non-sterile	10	26056
Adapter (Silicone), length 44mm	1	26146
Adapter support (PP), length 49mm	1	26220
Suction bellows (Silicone) with screw ring (PP)	1	26225
Valve system (PP, PTFE, Silicone)	1	26128







Effortless Pipetting



Filling

Squeeze the suction bellows. It allows aspiration up to 50ml with one compression. The fill rate is continuously variable with the pipetting lever.



Delivery

To discharge the liquid, simply press down the lever. The valve system is designed so that flow rate does not affect accuracy.



Blow-out function When using blow-out pipettes, press the convenient blowout bulb once the meniscus has come to rest in the pipette tip. Pipetting has never been easier.



Toll Free: 888-522-2726 www.brandtech.com