Transferpette® *S* Single- & multichannel pipettes from BRAND

Transferpette[®] \mathcal{S} pipettes set the benchmark for premium performance, light weight, comfort and easy service.

- Thumb-tip volume selection Set and secure the volume without even shifting your hand position!
- Short pipetting stroke Shortest range of pipetting motion among premium pipettes reduces risk of repetitive strain injury
- 4-digit display Precise settings that are always visible while pipetting
- Fully autoclavable at 121°C Repeatedly autoclavable without disassembly or recalibration
- Light weight and rugged Made with precision advanced composites for chemical resistance, dimensional stability and light weight
- Full pipetting range Adjustable and fixed-volume single channels pipette volumes from 0.1µL to 10mL; multichannels from 0.5µL to 300µL
- Economical Fast, in-house cleaning, repair and calibration—without tools for long, economical service

Lightweight...Precise... Rugged...Reliable...



Toll Free: 888-522-2726 www.brandtech.com



The Transferpette[®] \mathcal{S} family of pipettes provides unparalleled comfort and ease-of-use in a central-button pipette.

- Innovative materials reduce weight, improve corrosion resistance and protect accuracy, even after repeated autoclaving.
- Short pipetting stroke reduces the risk of RSI (repetitive strain injury), and enhances comfort for operators with smaller hands. Curved finger rest supports pipette for a relaxed grip.
- True one-handed operation. Volume can be set and secured with the tip of the thumb - even while wearing gloves.
- Large separate tip ejector for reduced tip ejection forces.
- Advanced composite pistons in multichannel models are light, dimensionally stable and corrosion resistant.
- Volume range 0.1µL to 10mL for single channel models; 0.5µL to 300µL for multichannels.
- CE-IVD compliant.



Simple, economical, in-lab service

Transferpette[®] *S* eight- and twelve-channel pipettes feature patented individually removable tip cones for easy cleaning and seal replacement. This is especially handy if faults are discovered during calibration, as only the individual channel needs service.

Transferpette[®] *S* single- channel pipettes can be disassembled for cleaning and reassembled in seconds without tools. Integrated spring/seal wear part simplifies in-lab service.

Comfortable

Broad, curved tip-ejector butte

Secure

A volume brake helps protect accidental volume changes.

Clearly accurate

4-digit display for precise volu always remains visible during

Color coded Easy selection of the right tip.

Maximum compatibility

Tip cone design offers excellent fit with BRAND tips and broadest compatibility with tips from other manufacturers.



Short stroke length reduces strain

Up to 40% shorter range-of-motion than competitive pipettes.

Fast

One-handed volume setting for both right- and left-handed users - even with gloves!

Reduced static strain

Pipette suspends from relaxed hand.

Calibration adjustment without tools

Easy Calibration[™] makes it easy. Adjustment from factory settings is clearly visible from the outside (according to ISO 8655).

Fully autoclavable

Both single and multichannel models are autoclavable at 121°C (20 min) without disassembly for maximum convenience and protection from contamination!

> Smooth operation Specially selected sealing material provides uniformly smooth pipetting stroke.

Low strain

Resilient V-rings and the stepped design of the tip ejector reduce tip mounting and ejection forces. V-rings support broad tip compatibility.



วท

against

me settings;

pipetting.

Transferbette® S

Convenient Manifold rotates 360° in both directions allowing you to pipette from any angle.



Easy thumb-tip volume setting



Covered nameplate identifies pipettes without messy tape!




Red recalibration flag indicates adjustment from factory specifications



Free shelf mount with Transferpette[®] S single or multichannel pipettes



Carousel stand for handy storage of up to six Transferpette® S single or multichannel pipettes



Transferpette® S Adjustable Volume Single Channel Pipettes



	-					2015
Capacity, µL	Model	$A^{\star} < \pm \%$	$CV^* \leq \%$	Subdivision, µL	Cat. No.	List Price
0.1-1	D-1	2	1.2	0.001	704768	\$342.00
0.1-2.5	D-2.5	1.4	0.7	0.002	704769	311.00
0.5-10	D-10	1	0.5	0.01	704770	311.00
2-20	D-20	0.8	0.4	0.02	704772	311.00
10-100	D-100	0.6	0.2	0.1	704774	311.00
20-200	D-200	0.6	0.2	0.2	704778	311.00
100-1000	D-1000	0.6	0.2	1	704780	311.00
500-5000 (0.5-5mL)	D-5000	0.6	0.2	5	704782	311.00
1000-10000 (1-10mL)	D-10000	0.6	0.2	10	704784	311.00
Transferpette® S Fi	xed Volume Single	e Channel Pipettes	5			
10	F-10	1	0.5	_	704708	169.00
20	F-20	0.8	0.4	—	704716	169.00
25	F-25	0.8	0.4	—	704720	169.00
50	F-50	0.8	0.4	—	704728	169.00
100	F-100	0.6	0.2	—	704738	169.00
200	F-200	0.6	0.2	_	704744	169.00
500	F-500	0.6	0.2	—	704754	169.00
1000	F-1000	0.6	0.2	—	704762	169.00
Transformatta® € Single channel pin	ottop are supplied with performa	aco cortificato, oporating manual	cholf mount and throos	(oar warrant)		

Transferpette® S Single channel pipettes are supplied with performance certificate, operating manual, shelf mount and three year warranty

Transferpette® S Single Channel Starter Sets



			2015
Starter Set	Includes following Transferpette® ${\cal S}$ models	Cat. No.	List Price
Micro	D-1, D-10, D-100	704790	\$745.00
Mid-Size	D-20, D-200, D-1000	704791	745.00
Macro	D-1000, D-5000, D-10000	704792	745.00
Standard	D-10, D-100, D-1000	704793	745.00

Starter Sets include three pipettes with performance certificates, operating manual, three shelf mounts, and three filled Tip-Boxes with appropriate sized tips.

Transferpette® S -8/-12 Multichannel Pipettes

Capacity, µL**	$A^* < \pm \%$	$CV^* \le \%$	Subdivision, µL	Transferpette [®] <i>S</i> -8 Channel	2015 List Price	Transferpette® <i>S</i> -12 Channel	2015 List Price
0.5-10	1.6	1.0	0.01	703700	\$760.00	703720	\$938.00
5-50	0.8	0.4	0.1	703706	760.00	703726	938.00
10-100	0.8	0.3	0.2	703708	760.00	703728	938.00
20-200	0.8	0.3	0.2	703710	760.00	703730	938.00
30-300	0.6	0.3	0.5	703712	760.00	703732	938.00

Transferpette® S-8/-12 pipettes supplied with performance certificate, operating manual, shelf mount, two tip boxes, reagent reservoir, pack of replacement V-rings. One-year warranty.

Accessories

3

10-0

		2015
	Cat. No.	List Price
Carousel Stand - for up to six Transferpette® <i>S</i> single or multichannel pipettes, pack of 1	704805	\$134.00
Individual Multichannel Stand - for all Transferpette® G, Transferpette® electronic and Transferpette® multichannel pipettes, pack of 1	703440	38.00
Shelf Mount - for all Transferpette® S single or multichannel pipettes, pack of 1	704810	28.00
Autoclavable Reagent Reservoirs - PP, with translucent lids, pack of 10	703459	33.00
Autoclavable Reagent Reservoirs - PP, sterile, individually wrapped, 100 pieces total	703411	274.00
Autoclavable Reagent Reservoirs - PP, sterile, 40 packs of five, 200 pieces total	703409	251.00
A*=Accuracy, CV*=Coefficient of Variation		

* The value of accuracy and coefficient of variation are final test values referring to the delivered nominal volume, instrument and distilled water at equilibrium with ambient temperature (20°C/68°F) and with smooth operation.

Complete line of tips available (sterile, non-sterile, filter & ultra low retention), visit brandtech.com for details.





Toll Free: 888-522-2726 www.brandtech.com

Lab Rats Trust BrandTech!